

....

DuraPack[®] 5000

High-Compaction Rear Loader

Environmental Solutions Group® A _ DOVER COMPACT

The unrivaled workhorse of the waste industry.

WE NEVER STOP WORKING FOR YOU

N

5

www.Heil.com

DuraPack[®] 5000

The unrivaled workhorse of the industry.

With nearly 30 years of reliability and over 20,000 units built, the Heil[®] **DuraPack** 5000 high-compaction refuse vehicle has become the mainstay of collection fleets, from small independent haulers to the world's largest municipal fleet.

Built to last. The **DuraPack** 5000 features the **Heil DuraPack** body, which includes a fully welded, interlaced subframe. With formed channels for extra strength, high tensile strength steel to maximize performance at a minimum weight, and full welding for superior resistance to corrosion and cracking, the **DuraPack** 5000 is a sturdy package with the stamina to absorb years of tough hauling.

Outstanding weight distribution. Incorporating a high cylinder mount into a compact design with a short overhang creates outstanding weight distribution and reduced wear on rearward chassis components. This maximizes forward loading of both the body and the payload.

2020 Controller Refresh. Now, the **Heil** In-Sight Display provides enhanced troubleshooting capabilities that can all be performed from within the safety of the cab. This is made possible by the recently upgraded remote mobile controller, which eliminates the need for a PDC box. The mobile controller provides two-way communications, and critical information directly to the display, eliminating relays and associated failures. All incab switches are conveniently located within the **Heil** In-Sight Display. This enhanced design allows for future additions, which in the past would have required the addition of an inconveniently placed auxiliary switch, on an already crowded dash. Now all this can be done in one, easy to access, in-cab display.

The Heil[®] **DuraPack**[®] **5000** Design, performance and reliability that works for YOU.





0000

Add 3rd Eye® Digital Packages Connect for service verification, body/chassis data, fuel tax reporting, and route management. Includes factory installed 3rd Eye Mobile, with the ability to connect up to eight cameras.



Add Roof Or Front Of Body CNG System Our system enables your CNG refuse fleet to deliver the same productivity you would expect from a diesel unit, while saving money with clean, domestic, compressed natural gas as fuel.



HHH

Add 3rd Eye[®] Collision Avoidance Radar 3rd Eye family of Integrated Collision Avoidance Radar Systems protect both your drivers, your assets, and those in close proximity to your vehicle, using existing 3rd Eye Mobile camera cables.



Add Bayne Thinline[®] Premium Cart Tippers Outfit your truck with a single or dual Bayne Thinline[®] premium mobile lifters and reduce the stress and strain on personnel who manually load the vehicle, and increase route efficiency.

Smarter By Design, With Loyalty Built In

The DuraPack® 5000 was specifically designed to maximize your efficiency on daily collection routes.

DuraPack[®] 5000



Reliable Rear Loader Performance

+ IN-SIGHT DISPLAY

The 2020 controller refresh allows for enhanced troubleshooting from the safety of the cab. This refresh also moved all in-cab switches to the In-Sight Display, allowing for constant modification.



+ SOLID FOUNDATION

The interlaced subframe, and frame mounted oil tank provide exceptional strength and durability, which means your **DuraPack** 5000 will enjoy a long lifespan.

+ TIME SAVER

The **DuraPack** 5000 features a flat, abrasion-resistant steel floor, which eliminates the messy job of cleaning trash buildup out of dirty troughs.

+ SUPERIOR FILTRATION

Our three-micron filtration system keeps oil cleaner, and extends the life of hydraulic components. Other manufacturers use 10-micron filtration, which can allow particulate matter to damage the hydraulic system.

+ ONE-HANDED MANUAL PACKING

Convenient one-handed manual controls stop, start, or reverse the upper panel or sweep panel at any point in the packing cycle.

Discover What Sets The DuraPack® Apart



HIGH CAPACITY HOPPER

The generous 3.94 cubic yard hopper can accommodate large items with ease, and requires less cycling on the route.



DURABILITY AND LONGEVITY

Our exclusive, fully welded, interlaced subframe provides exceptional longevity, while resisting abrasion, corrosion, and salt damage. The body is constructed of 7-8 ga. high tensile strength steel, while the hopper features 5/16" thick AR400 steel on the floor, and 3/16" thick AR400 steel on the sides for superior strength and durability.



MORE PACKING POWER

The Heil[®] Linkage Packing System is a proven performer. It has no rollers, slides, or slide shoes to wear out. Smaller cylinders deliver considerably more packing power for increased payloads.



SERVICE SMART SIDE DOOR

Our Service Smart design simplifies routine maintenance, keeping your truck away from the shop, and out servicing your customers, making money. The side door provides easy access for common maintenance tasks.

Smarter By Design, With Loyalty Built In

The DuraPack® 5000 was specifically designed to maximize your efficiency on daily collection routes.



Performance Specification	ons	
Compaction	1,000+ lbs. per yd ³	
Hopper Size	3.94 yd ³	
Packing Cycle Time	16-18 seconds*	
Reload Time	6-8 seconds*	
* with fast cycle pump option		

All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written Warranty Statement for this product at the time of shipment.

Hydraulic Specifications				
PUMP				
Туре	High pressure gear			
Maximum Operating Pressure	2,500 psi			
GPM	42 GPM			
OIL RESERVOIR				
Tank Capacity (net)	50 gallons (190 liters)			
Filters	3 micron return filter with in-cab filter monitor; 140 micron suction line			
VALVES				
Shutoff	Ball valve in suction line between pump and reservoir			
Packing Control	Spool type			
Ejector and Tailgate Raise	Spool type			

Tailgate Specifications		
Henney Conceit:	yd ³	3.94
Hopper Capacity	m ³	3.01
Sill Height Below Chassis Frame	in.	3.8
	mm	97
Hopper Loading Width	in.	80
Hopper Loading Width	mm	2,032
Hopper Opening Height	in.	55
hopper opening height	mm	1,397
Cycle Time (seconds)	complete	16-18*
Cycle Time (seconds)	reload	6-8*
* with fast cycle pump option		

DuraPack® 5000 Specifications

Typical Chassis Configuration		18 yd ³	20 yd ³	25 yd ³	27 yd ³	32 yd ³		
Minimum GVW	Minimum GVWR (1)		48,000	51,000	54,000	57,000	62,000	
	Conventional	front	12,000	13,000	14,000	15,000	16,000	
Minimum CAM	/D	Conventional	rear	36,000	38,000	40,000	42,000	44,000
Willing GAV	Minimum GAWR	Cab Quar Engine	front	14,000	15,000	16,000	17,000	18,000
U U	Cab-Over Engine	rear	34,000	36,000	38,000	40,000	44,000	
Usable CA		in.	124-130	N/A	N/A	N/A	N/A	
		mm	3,149-3,302	N/A	N/A	N/A	N/A	
Usable CT	Hashie OT		in.	105-111	115-121	150-156	162-168	190-196
Usable CT		mm	2,667-2,819	2,921-3,073	3,810-3,962	4,115-4,267	4,826-4,978	
Minimum Dlotf	Minimum Platform		in.	32	51	51	51	51
		mm	813	1,295	1,295	1,295	1,295	

Heil Environmental does not recommend mounting any chassis that does not meet the minimum GWWR/GVARs outlined above. (1) If CA/CT is not as recommended, contact Heil Environmental for applicable weight distribution and GWWR/GVAR requirements.

Body Specifications		18 yd³	20 yd ³	25 yd ³	27 yd ³	32 yd ³	
Body Capacity	yd ³	18	20	25	27	32	
	m ³	13.7	15.3	19.1	20.6	24.4	
A HH H	in.	225	235	270	282	310	
Overall Length	mm	5,715	5,969	6,858	7,163	7,874	
Overall Lawath With Tailante Daired	in.	275	285	320	332	360	
Overall Length With Tailgate Raised	mm	6,985	7,239	8,128	8,433	9,144	
	in.	96					
Overall Width	mm	2,438					
	in.	96					
Overall Height Above Frame	mm	2,438					
Overall Height With Tailgate Raised	in.	207					
	mm	5,257					
Gross Weight (approximate)	lbs.	14,300	14,800	15,500	15,900	17,200	
	kg.	6,487	6,727	7,045	7,227	7,818	

Cylinder Specifications						
Body Cylinders	Туре	Model	Stages	Bore		
Tailgate Raise	Single Acting	ALL	1	in.	4	
		ALL	1	mm	102	
Packer Sweep	3-Stage Double Acting Telescopic	ALL	4	in	5.5	
				mm	140	
Upper Panel	Double Acting	ALL	1	in	5	
				mm	127	
Ejection	Double Acting	18, 20, 25, 27 yd ³	4	in	6	
				mm	152	
		0012	5	in	7	
		32 yd³		mm	178	

WE NEVER STOP WORKING FOR YOU

DuraPack® 5000

High-Compaction Rear Loader



EXPEDITE THE PURCHASE OF YOUR HEIL® UNIT THROUGH SOURCEWELL

Sourcewell Cooperative Purchasing Program has awarded Heil a nationally bid contract for "Solid Waste and Recycling Collection Equipment with Related Equipment, Accessories, and Supplies." Through the Heil contract, Sourcewell members can purchase any of the Heil line of refuse and recycling equipment, including front-loading, side-loading, and rear-loading refuse collection vehicles, without having to create an RFP and send the project through a time-consuming duplicate bid process. By using the existing nationally bid contract, members can receive the products they need more quickly and cost effectively. Best of all, Sourcewell membership is free! Qualified agencies can join online via the Sourcewell purchasing website at www.sourcewell-mn.gov. To find out more about purchasing Heil equipment via the Sourcewell contract, please contact your local Heil Dealer at www.heil.com/dealers.



RELY ON EXPERIENCED LOCAL SUPPORT

When you buy from **Heil**, you gain the aftermarket support of the industry's strongest network of dealers in North America. We stand behind our dealers, so you get the product support you need for the life of your products. Our dealers are also trained to help you find the best product for your particular route needs. To find the **Heil** dealer nearest you, visit: **www.heil.com/dealers**.



TRUST HEIL® CERTIFIED OEM PARTS

Heil Certified OEM parts are the most reliable replacement parts for **Heil** refuse collection vehicles. They're made following the exact specifications and production processes on the same assembly lines as the parts originally installed on the bodies. This means that they fit perfectly every time. **Heil** uses only the highest-quality materials for parts that last - minimizing costly downtime. For more information on parts, contact your **Heil** dealer. Visit: **www.heil.com/dealers** to find the dealer nearest you.





COUNT ON THE LOWEST TCC

Helping you save money is our passion, and we apply tremendous resources to advance our product and service offerings to improve the profitability of your business and provide the lowest Total Cost of Collection and the maximum return on your investment. You can be confident that choosing **Heil** equipment brings a longterm partnership with the industry leader.



CONFIGURATION ASSISTANCE

Chassis layout drawings are available through your local **Heil** dealer. To find your dealer, visit **www. heil.com/dealers.**



INDUSTRY-LEADING TRAINING

Heil has completely revamped their training programs with the addition of both the Heil Service Shack[™] and their four-tiered Nexteligence[™] Connected-Tech Training Program. Now, customers can visit the Heil Service Shack on the Heil website to learn the latest techniques and view helpful service and training videos any time, as well as sign up for Connected-Tech courses to better train technicians on Heil Refuse Products. Ensure your shops are servicing your Heil products correctly; check out the Heil training offerings at www.heil.com/nexteligence.