

DOVER

### WE NEVER STOP WORKING FOR YOU

## Heil<sup>®</sup> MultiPack<sup>®</sup>

Multi-Role Refuse Collection Vehicle

# S HEIL to 6 (III) N ใส่ utions Group® A DOVER COMPANY

### The one vehicle that can do it all.

www.Heil.com

## Heil<sup>®</sup> MultiPack<sup>®</sup>

#### The one vehicle that can do it all.

The **Heil MultiPack** refuse collection vehicle can do it all because it combines three precision-engineered products: the durable **Heil** DuraPack<sup>®</sup> body, the superior Python<sup>®</sup> automated arm, and the proven **DuraPack** 5000 tailgate. These features make the **MultiPack** the most versatile refuse collection vehicle. If you're looking for ways to reduce your total capital equipment costs, think **MultiPack**. It is the only vehicle that can handle rear loader, side loader, and even commercial routes single-handedly.

The **MultiPack** is ideal for routes with "unlimited-at-the-curb" contracts. It's also the perfect unit for those ugly "surprises" that unexpectedly end up next to a customer's cart on collection day. While other manufacturers may offer multi-function vehicles, only the **Heil MultiPack** is "totally functional" in both modes of operation because it can pick up a completely manual or automated route. Think of the possibilities!

If your routes need a strong right arm - you've found it. The **Python** automated arm can lift up to 800 pounds (625 pounds fully extended) and collect up to 1,400 homes per day. It also strikes quickly with an eight-second cycle time - one of the fastest in the industry, saving you up to four seconds per stop.

The **Python** arm features precision-crafted three-inch cushioned cylinders which enable it to operate smoothly, saving wear on the lift arm and the chassis. The arm has a nine-foot reach and makes cleaner pickups. Its fast action prevents spillage and consistently returns the cart with the lid closed.

The **MultiPack** also features the proven **DuraPack** body, which includes a fully welded, interlaced subframe. With formed channels for extra strength, high tensile strength steel to maximize performance at a minimum weight, and full welding for superior resistance to corrosion and cracking, the **DuraPack** body is built to last, with the stamina to absorb years of tough hauling.

To add this versatile performer to your fleet, contact your local **Heil** Dealer. To find the Dealer nearest you, please visit www.heil.com.

**The Heil<sup>®</sup> MultiPack<sup>®</sup>** Design, performance, and reliability that works for YOU.





Add 3rd Eye<sup>®</sup> Digital Packages Connect for service verification, body/chassis data, fuel tax reporting, and route management. Includes factory installed 3rd Eye Mobile, with the ability to connect up to eight cameras.



Add Bayne Thinline<sup>®</sup> Premium Cart Tippers Outfit your truck with a single or dual Bayne Thinline<sup>®</sup> premium mobile lifters and reduce the stress and strain on personnel who load the vehicle, and increase route efficiency.

Add 3rd Eye<sup>®</sup> Collision Avoidance Radar The 3rd Eye family of Integrated Collision Avoidance Radar Systems protect both your drivers, your assets, and those in close proximity to your vehicle using existing 3rd Eye Mobile camera cables.

Add Body Rooftop CNG Storage This optional system enables your CNG refuse fleet to deliver the same productivity you would expect from a diesel unit while saving money with clean, domestic, compressed natural gas as fuel.



## Smarter By Design, With Loyalty Built In

The MultiPack® was specifically designed to accommodate highly variable routes, quickly and efficiently.

## Heil<sup>®</sup> MultiPack<sup>®</sup>

 ★ EXCEPTIONAL REACH AND LIFT - The patented automated Python<sup>®</sup> arm can reach up to nine feet. Able to lift up to up to 800 pounds, the Python arm features cushioned cylinders for smooth action, saving wear and tear on both the lift arm and the chassis. The Python arm's unique lift geometry enables the arm to consistently return carts with the lids closed.

QUIET, FUEL-EFFICIENT OPERATION - The Heil Operate-in-Gear-at-

- Idle System comes standard on the MultiPack. It is designed to help you finish routes up to 20% faster, saving up to one gallon of fuel per hour while reducing wear on the lift assembly, chassis, engine, and transmission. Plus, it greatly reduces noise a benefit to operators and customers alike, especially in residential neighborhoods.
- + SERVICE SMART SIDE DOOR Our Service Smart design simplifies routine maintenance, keeping your truck away from the shop and out servicing your customers, making money. The side door provides easy access for common maintenance tasks.
- + **TIME SAVER** The **DuraPack** body features a flat, abrasion-resistant steel floor, which eliminates the messy job of cleaning trash buildup out of dirty troughs.
- HIGH-CAPACITY HOPPER The generous 3.94 cubic yard tailgate hopper can accommodate large items with ease, and requires less cycling on the route.

### **Reliable Automated Side Loader Performance**

- ★ SOLID FOUNDATION Our exclusive fully welded, interlaced subframe provides exceptional longevity, while resisting abrasion, corrosion, and salt damage. The body is constructed of 7-8 ga. high tensile strength steel, while the tailgate hopper features 5/16" thick AR400 steel on the floor and 3/16" thick AR400 steel on the sides for superior strength and durability.
- + **ONE-HANDED MANUAL PACKING** The convenient one-handed manual controls located on the tailgate stop, start, or reverse the upper panel or sweep panel at any point in the packing cycle.
- + JOYSTICK CAB CONTROLS Reliable, ergonomic joystick controls deliver smoother performance and enhanced usability. With the AutoLoad system, the operator can reach, grab, lift, dump, and return the arm to the stowed position using only the joystick and two buttons.
- + **DURAMOUNT DESIGN** The Heil DuraMount Design, used to mount the lift to the chassis frame, reduces the potential for bolt fatigue and provides Service Smart bolt access for easy maintenance.

#### **Discover What Sets The Heil® MultiPack® Apart**



#### **MULTI-FUNCTION SPECIALTY VEHICLE**

The **MultiPack** is the one refuse collection vehicle that can handle rear loader, side loader, and even commercial routes single-handedly.



**PYTHON® AUTOMATED LIFT** 

Eight-second lift cycle can save up to four seconds per stop - up to one hour per day. This can add up to more than \$15,000 in savings per truck, per year! The **Python** lift arm's nine-foot reach can slither between cars and other obstacles, making even the most difficult pick-ups possible.



DURABILITY AND LONGEVITY

Our exclusive, fully welded, interlaced subframe provides exceptional longevity, while resisting abrasion, corrosion, and salt damage. The body is constructed of 7-8 ga. high tensile strength steel, while the hopper features 5/16" thick AR400 steel on the floor, and 3/16" thick AR400 steel on the sides for superior strength and durability.



#### **MORE PACKING POWER**

The **Heil** Linkage Packing System is a proven performer. It has no rollers, slides, or slide shoes to wear out. The optimized geometry allows smaller, lighter cylinders to obtain the same packing power and payloads that usually require larger, heavier, and more expensive cylinders.

## **Smarter By Design, With Loyalty Built In**

The MultiPack® was specifically designed to accommodate highly variable routes, quickly and efficiently.

## Heil<sup>®</sup> MultiPack<sup>®</sup> Specifications

Performance Specifications		
Lift Capacity	800 lbs.	
Lift Cycle Time*	8 seconds	
Lift Reach	9 ft.	
Compaction	Up to 1,000 lbs. per yd <sup>3</sup>	
Working RPM	750 (operate-in-gear-at-idle)	
* Complete cycle time defined as grip, dump, return and release		

Cylinder Specifications					
Body Cylinders	Туре	Bore x Stroke			
Tailgate Raised	(2) Double acting	in.	4.0 x 26		
Taligate Halsed		mm	102 x 660		
Packer Sweep (tailgate)	(2) Single acting	in	5.5 x 24		
		mm	140 x 609		
Upper Panel (tailgate)	(2) Double acting	in	5.0 x 26		
		mm	127 x 914		
Packer/Ejector (eject model)	(2) Double acting	in.	5.5 x 141		
Packer/Ejector (eject model)		mm	140 x 3,581		
Lift Cylinders					
Reach	(1) Double acting	in.	3.1 x 16.0		
Reach		mm	80 x 406		
Grab	(1) Double acting	in.	3.1 x 8.0		
		mm	80 x 203		
Lift	(1) Double acting	in.	3.0 x 16.0		
	(i) Double acting	mm	80 x 406		

Hydraulic Specifications			
PUMP	Operate-In-Gear-At-Idle (standard)		
Туре	Tandem Vane front		
Maximum Operating Pressure	2,300 psi (15,858 kPa)		
Working RPM	750 RPM approx.		
Flow at Working RPM	28 GPM (106 LPM) approx.		
OIL RESERVOIR	Chassis frame mounted		
Gross Capacity	50 gallons (190 liters)		
Filters	Return line 3 micron, 140 micron suction strainer		
VALVES			
Packing Control	Electric, push button operated		
Tailgate			
Tailgate Locking	Air operated toggle		
Body Raise			

Automated Lift Specifications		
Lift Capacity	800 lbs.	
Cycle Time	8 seconds @ idle	
Reach	9 ft.	
Ground Clearance	20 in. from ground to bottom of grabber arms (based on a 42 in. chassis rail height)	
Weight*	1,850 lbs. approx.	
Controls	Joystick, air over hydraulic with feathering ability	
* Weight includes standard 60/90 gallon grabbers		

Typical Chassis Configuration*			<b>24 yd</b> <sup>3</sup>
Min. GVWR (1)		lbs.	56,000
Min. GAWR	Front	lbs.	18,000
	Rear	lbs.	44,000
Usable CT		in.	190 ± 6
Wheelbase		in.	215±6

Specify chassis, engine, and transmission upon entering order.

Chassis must have front engine crankshaft adapter for front drive gear pumps.

Any truck requiring special alterations, moving battery boxes, oil tanks, etc., will not be made until a letter authorizing these changes has been received by Heil Environmental.
 OPENATE IN OPEN with provide 000 fe line of entering with internet activity with internet activity of the provide 000 fe line of entering of e

Body Specifications		<b>24 yd</b> <sup>3</sup>	
Body Capacity		yd <sup>3</sup>	24
		m3	18.3
Front of Body Hopper Capacity		yd <sup>3</sup>	5.2
		m3	4.0
Overall Length*		in.	332
		mm	8,435
Overall Length (Tailgate Raised)*		in.	372
		mm	9,450
Overall Width		in.	96
		mm	2,440
	body lowered	in.	96
Overall Height Above Frame		mm	2,440
	body raised	in.	208
		mm	5,285
Gross Weight (Route Ready, Without Options)		lbs.	21,000
		kg.	9,530

All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written Warranty Statement for this product at the time of shipment.



## Heil<sup>®</sup> MultiPack<sup>®</sup>

The one vehicle that can do it all.



#### EXPEDITE THE PURCHASE OF YOUR HEIL® UNIT THROUGH SOURCEWELL

Sourcewell Cooperative Purchasing Program has awarded Heil a nationally bid contract for "Solid Waste and Recycling Collection Equipment with Related Equipment, Accessories, and Supplies." Through the Heil contract, Sourcewell members can purchase any of the Heil line of refuse and recycling equipment, including front-loading, side-loading, and rear-loading refuse collection vehicles, without having to create an RFP and send the project through a time-consuming duplicate bid process. By using the existing nationally bid contract, members can receive the products they need more quickly and cost effectively. Best of all, Sourcewell membership is free! Qualified agencies can join online via the Sourcewell purchasing website at www.sourcewell-mn.gov. To find out more about purchasing Heil equipment via the Sourcewell contract, please contact your local Heil Dealer at www.heil.com/dealers.



#### RELY ON EXPERIENCED LOCAL SUPPORT

When you buy from **Heil**, you gain the aftermarket support of the industry's strongest network of dealers in North America. We stand behind our dealers, so you get the product support you need for the life of your products. Our dealers are also trained to help you find the best product for your particular route needs. To find the **Heil** dealer nearest you, visit: **www.heil.com/dealers**.



#### **TRUST HEIL® CERTIFIED OEM PARTS**

**Heil** Certified OEM parts are the most reliable replacement parts for **Heil** refuse collection vehicles. They're made following the exact specifications and production processes on the same assembly lines as the parts originally installed on the bodies. This means that they fit perfectly every time. **Heil** uses only the highest-quality materials for parts that last - minimizing costly downtime. For more information on parts, contact your **Heil** dealer. Visit: **www.heil.com/dealers** to find the dealer nearest you.





#### **COUNT ON THE LOWEST TCC**

Helping you save money is our passion, and we apply tremendous resources to advance our product and service offerings to improve the profitability of your business and provide the lowest Total Cost of Collection and the maximum return on your investment. You can be confident that choosing **Heil** equipment brings a longterm partnership with the industry leader.



#### **CONFIGURATION ASSISTANCE**

Chassis layout drawings are available through your local **Heil** dealer. To find your dealer, visit **www. heil.com/dealers.** 



#### **INDUSTRY-LEADING TRAINING**

Heil has completely revamped their training programs with the addition of both the Heil Service Shack<sup>™</sup> and their four-tiered Nexteligence<sup>™</sup> Connected-Tech Training Program. Now, customers can visit the Heil Service Shack on the Heil website to learn the latest techniques and view helpful service and training videos any time, as well as sign up for Connected-Tech courses to better train technicians on Heil Refuse Products. Ensure your shops are servicing your Heil products correctly; check out the Heil training offerings at www.heil.com/nexteligence.

© Copyright 2021 The Heil Co. All rights reserved